



ID 3.0"
COILOVER SPRINGS

STRAIGHT TYPE

PART NUMBER	SPRING RATE		USABLE STROKE		MAX STORKE		MAX. LOAD		WEIGHT	
	lbs/inch	kgf/mm	inch	mm	inch	mm	lbs	kg	lbs	kg
12" LENGTH										
120-300-150	150	2.7	8.1	207	8.8	224	1,323	600	3.28	1.49
120-300-175	175	3.1	7.8	197	8.7	222	1,530	694	3.51	1.59
120-300-200	200	3.6	7.5	191	8.6	219	1,724	782	3.79	1.72
120-300-225	225	4.0	7.3	186	8.5	215	1,905	864	4.12	1.87
120-300-250	250	4.5	7.2	184	8.3	211	2,077	942	4.50	2.04
120-300-275	275	4.9	7.2	182	8.1	206	2,230	1,012	4.89	2.22
120-300-300	300	5.4	7.2	182	7.9	200	2,362	1,071	5.36	2.43
120-300-325	325	5.8	6.9	176	7.9	201	2,572	1,167	5.42	2.46
120-300-350	350	6.3	6.8	173	7.8	198	2,728	1,238	5.73	2.6
120-300-375	375	6.7	6.9	175	7.5	191	2,820	1,279	6.31	2.86
120-300-400	400	7.1	6.7	171	7.5	191	3,008	1,364	6.44	2.92
120-300-425	425	7.6	6.7	170	7.4	187	3,129	1,419	6.81	3.09
120-300-450	450	8.0	6.7	170	7.2	182	3,224	1,463	7.23	3.28
120-300-475	475	8.5	6.7	170	7.0	178	3,329	1,510	7.67	3.48
120-300-500	500	8.9	6.5	166	7.0	177	3,484	1,580	7.87	3.57
14" LENGTH										
140-300-150	150	2.7	9.1	231	10.3	261	1,541	699	3.99	1.81
140-300-175	175	3.1	9.0	228	9.9	252	1,736	788	4.63	2.10
140-300-200	200	3.6	8.7	220	9.8	249	1,961	889	4.96	2.25
140-300-225	225	4.0	8.4	214	9.6	245	2,170	984	5.34	2.42
140-300-250	250	4.5	8.3	210	9.5	241	2,372	1,076	5.75	2.61
140-300-275	275	4.9	8.1	207	9.3	235	2,544	1,154	6.24	2.83
140-300-300	300	5.4	8.0	202	9.2	233	2,752	1,248	6.53	2.96
140-300-350	350	6.3	7.8	199	8.8	224	3,087	1,400	7.45	3.38
140-300-400	400	7.1	7.5	191	8.7	220	3,465	1,572	7.98	3.62
140-300-450	450	8.0	7.3	185	8.5	215	3,809	1,728	8.60	3.90
140-300-500	500	8.9	7.2	182	8.2	209	4,114	1,866	9.30	4.22
140-300-550	550	9.8	7.1	180	8.0	202	4,374	1,984	10.10	4.58
140-300-600	600	10.7	7.0	179	7.7	195	4,606	2,089	11.00	4.99
16" LENGTH										
160-300-250	250	4.5	9.4	238	10.5	266	2,618	1,188	7.34	3.33
160-300-300	300	5.4	8.9	227	10.2	258	3,047	1,382	8.20	3.72
160-300-350	350	6.3	8.6	218	10.0	253	3,486	1,581	8.95	4.06
160-300-400	400	7.1	8.5	216	9.5	241	3,795	1,722	10.19	4.62
160-300-450	450	8.0	8.0	202	9.6	245	4,341	1,969	10.19	4.62
160-300-500	500	8.9	7.8	198	9.4	239	4,705	2,134	10.98	4.98
160-300-550	550	9.8	7.7	196	9.1	232	5,024	2,279	11.84	5.37

All the specs above are subject to change without any notice.



Swift Springs USA Inc. 1850 S. Carlos Ave. Ontario, CA 91761
 Phone: (909) 923-9788 Fax: (909) 923-9798 www.SwiftSprings.com

THE SCIENCE OF WINNING

PART NUMBER	SPRING RATE		USABLE STROKE		MAX STORKE		MAX. LOAD		WEIGHT	
	<i>lbs/inch</i>	<i>kgf/mm</i>	<i>inch</i>	<i>mm</i>	<i>inch</i>	<i>mm</i>	<i>lbs</i>	<i>kg</i>	<i>lbs</i>	<i>kg</i>
18" LENGTH										
180-300-250	250	4.5	10.4	263	11.5	293	2,884	1,308	8.91	4.04
180-300-300	300	5.4	10.0	255	11.1	281	3,319	1,505	10.25	4.65
180-300-350	350	6.3	9.7	247	10.6	270	3,720	1,688	11.46	5.20
180-300-400	400	7.1	9.4	240	10.4	263	4,142	1,879	12.48	5.66
180-300-450	450	8.0	8.7	220	10.7	273	4,837	2,194	12.04	5.46
180-300-500	500	8.9	8.5	215	10.5	267	5,256	2,384	12.87	5.84

All the specs above are subjct to change without any notice.